

View Online at <https://aerobasegroup.com/nsn/6625-01-023-7092>

Overall Length:

12.030 inches

Overall Height:

4.950 inches

Overall Width:

5.300 inches

Current Type:

Ac

Cubic Measure:

280.977 cubic inches

Voltage Rating:

350.0 volts

Beam Quantity:

2

Graduation Interval:

Graduated in v/div on y-axis; graduated in sec/div on x-axis

Mounting Method:

Cradle in cabinet

Screen Size:

2.500 by 2 inches

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.0/+15.0 megahertz

Single Trigger Sweep Duration:

Between 0.2 microseconds and 0.5 seconds

Trigger Sweep Voltage Amplitude Rating:

250.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.2 usec; 0.5 usec; 1 usec; 2 usec; 5 usec; 10 usec; 20 usec; 50 usec; 0.1 msec; 0.2 msec; 0.5 msec; 1 msec; 2 msec; 5 msec; 10 msec; 20 msec; 50 msec; 0.1 sec; 0.2 sec; 0.5 sec

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Not provided

Amplifier Input Impedance Rating Provision:

Provided

Y-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Criticality Code Justification:

Supp

Special Features:

X 10 magnifier for sweep rates to 20 nsec/div

Supplementary Features:

Critical application: support equipment, b-1 aircraft; test set, mvs, an/tam-3a; missile, tow; tank, sheridan m-551

Specification Data:

18876-10186172 manufacturers specification control

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g