NSN 6625-01-024-2929

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-024-2929

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.500 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

50 single indicator 2nd range

Overall Diameter:

3.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hardware included

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges and green single indicator all ranges and red single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.460 inches

Meter Body Diameter Behind Mounting Flange:

2.670 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

NSN 6625-01-024-2929

Ammeter - Page 2 of 2



green

Power Source	:
External	
Mounting Faci	lity Type And Quantity:
3 screw and 3 u	unthreaded hole
Scale Graduat	ion Type:
Linear single in	dicator all ranges
Measurement	Range:
+0.0/+50.0 amp	peres, ac single indicator 2nd range
Scale Selectio	n Method:
Terminal	
Features Prov	ided:
Magnetic shield	and zero adjuster
Movement Sus	spension Method:
Jewel pivot bas	e
Circuit Attach	ment Method And Quantity:
2 threaded stud	1
Special Featur	res:
Ruggedized	
Special Markir	ngs:
0 to 100 millian	nperes increments are red; 0 to 50 amperes are in black; 0 to 2 increments are
Material:	
Steel	
Nuclear Hardn	ess Critical Feature:
Nonhardened	
Surface Treatr	nent:
Paint	
Special Test F	eatures:
Complies with r	nil-m-10304
Style Designat	tor:
Round flush mt	g
Fsc Applicatio	n Data:
Test set, elect.	Equip.
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	n:
No	
Fiig:	
A310a0	