

View Online at <https://aerobasegroup.com/nsn/6625-01-024-9283>

Circuit Current For Which Designed:

Dc

Overall Length:

7.039 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.346 inches and 3.406 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Mounting Hole Diameter:

Between 0.311 inches and 0.318 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Cold resistant and corrosion resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

End Application:

Control-indicator, general status; litton systems inc. Model 792550

Furnished Items And Quantity:

Nut 8; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

10.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

6.320 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+2500.0 kilowatts single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Red line at 2000 amperes

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Environmental requirements per mil-m-16034

Style Designator:

Rectangular flush mtg

Supplementary Features:

Ambient pressure: 27.5 plus or minus 3.5 inches of mercury; impedance: 1000 ohms per volt

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0