

View Online at <https://aerobasegroup.com/nsn/6625-01-024-9283>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

7.039 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.346 inches and 3.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 3.346 inches and 3.406 inches

**Overall Height:**

Between 4.250 inches and 4.750 inches

**Overall Width:**

Between 4.250 inches and 4.750 inches

**Mounting Hole Diameter:**

Between 0.311 inches and 0.318 inches

**Scale Division Quantity:**

50 single indicator single range

**Environmental Protection:**

Cold resistant and corrosion resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

**End Application:**

Control-indicator, general status; litton systems inc. Model 792550

**Furnished Items And Quantity:**

Nut 8; washer 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 volts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5/+1.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

6.320 inches

**Meter Body Diameter Behind Mounting Flange:**

3.980 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+2500.0 kilowatts single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Red line at 2000 amperes

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Environmental requirements per mil-m-16034

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Ambient pressure: 27.5 plus or minus 3.5 inches of mercury; impedance: 1000 ohms per volt

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0