

View Online at <https://aerobasegroup.com/nsn/6625-01-024-9285>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

7.465 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 6.045 inches and 6.055 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.680 inches and 1.690 inches

**Overall Height:**

2.490 inches

**Overall Width:**

6.690 inches

**Scale Division Quantity:**

36 single indicator all ranges

**Mounting Stud Length:**

Between 1.000 inches and 1.250 inches

**Environmental Protection:**

Cold resistant and drip proof and heat resistant and salt spray resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Term. Hdw 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 volts

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

5.720 inches

**Meter Body Width Behind Mounting Flange:**

5.430 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+180.0 pounds per square inch single indicator 2nd range

**Mounting Stud Diameter:**

0.190 inches

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

2.170 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Vert mtg

**Fsc Application Data:**

Test set, electronic systems, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0