

View Online at <https://aerobasegroup.com/nsn/6625-01-024-9286>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

7.465 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 6.045 inches and 6.055 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.680 inches and 1.690 inches

**Overall Height:**

2.490 inches

**Overall Width:**

6.690 inches

**Scale Division Quantity:**

75 2nd indicator single range

**Mounting Stud Length:**

Between 0.100 inches and 0.125 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 8; washer 8

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 volts

**Dial Scale Marking Color:**

Black all indicators all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale all indicators all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

5.720 inches

**Meter Body Width Behind Mounting Flange:**

5.430 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White all indicators all ranges

**Pointer Color:**

Red all indicators all ranges

**Scale Marking:**

Left scale: degrees f x 10 to 2nd power, 0, 2, 4, 6, 8, 10, 12, 14, 16, 18, 20; right scale: psia, 0, 5, 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear all indicators all ranges

**Mounting Stud Diameter:**

0.190 inches

**Meter Body Height Behind Mounting Flange:**

2.170 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Vert mtg

**Fsc Application Data:**

Test set, electronic systems, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0