## NSN 6625-01-026-6506

Null Meter - Page 1 of 2

**Movement Type:**Moving iron vane



View Online at https://aerobasegroup.com/nsn/6625-01-026-6506

view Offilitie at https://derobasegroup.com/hsr//0025-01-020-0300
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.870 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.870 inches
Overall Height:
2.375 inches
Overall Width:
2.364 inches
Scale Division Quantity:
30 single indicator single range
Mounting Stud Length:
0.500 inches
Environmental Protection:
Airtight and dust resistant and heat resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water
resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
200.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
0.947 inches
Meter Body Diameter Behind Mounting Flange:
2.066 inches

## NSN 6625-01-026-6506

Null Meter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:
3; -2; -1; 0; +1; +2; +3
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.109 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On back, made in usa
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0