NSN 6625-01-026-8841

Wattmeter - Page 1 of 2

Circuit Current For Which Designed:

Ac

Overall Length: 5.312 inches Overall Height: 4.000 inches Overall Width: 4.625 inches

Scale Division Quantity:



View Online at https://aerobasegroup.com/nsn/6625-01-026-8841

| 30 single indicator single range |
|---|
| Frequency Rating: |
| 60.0 hertz |
| Mounting Stud Length: |
| 0.500 inches |
| Distance Between Mounting Facility Centers: |
| 3.750 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Two hole/stud |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.000/+2.000 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.922 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.790 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+600.0 watts single indicator single range |

NSN 6625-01-026-8841

Wattmeter - Page 2 of 2



| Mounting Stud Diameter: |
|--|
| 0.164 inches |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 3 threaded stud |
| Operating Voltage Rating In Volts: |
| 120.0 ac |
| Phase: |
| Three |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Paint |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |