

View Online at <https://aerobasegroup.com/nsn/6625-01-029-5194>

Circuit Current For Which Designed:

Dc

Overall Length:

1.750 inches

Overall Height:

2.500 inches

Overall Width:

3.000 inches

Scale Division Quantity:

50 single indicator 1st range

Environmental Protection:

Dust resistant

End Application:

Landing craft air cushion (lcac), sturgeon class ssn (637), ticonderoga class cg (47), virginia class cgn (41), los angeles class ssn (688), forrestal class cv, nimitz class cvn, spruance class dd (963), radar, series an/sps-4 (v)

Furnished Items And Quantity:

Nut 2; shorting wire 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

White single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.301 inches

Meter Body Diameter Behind Mounting Flange:

2.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator all ranges

Pointer Color:

White single indicator all ranges

Power Source:

External

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-10.0 to 3.0 amperes single indicator 3rd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Weapon system essential

Material:

Plastic

Special Test Features:

Drawing iaw mil-std-100b

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0