

View Online at <https://aerobasegroup.com/nsn/6625-01-030-5341>

Circuit Current For Which Designed:

Ac

Overall Length:

6.150 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

25 single indicator single range

Frequency Rating:

Between 380.0 hertz and 420.0 hertz

Overall Diameter:

3.510 inches

Environmental Protection:

Cold resistant and dust resistant and fungus resistant and heat resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.750 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+50.0 milliamps single indicator single range

Features Provided:

Adjustable index pointer and zero adjuster

Circuit Attachment Method And Quantity:

20 pin

Operating Voltage Rating In Volts:

Between 108.0 ac and 132.0 ac

Special Features:

Output is a dpdt relay contact rating 1 amp at 28 vdc

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Meter resistance 50.0 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0