## NSN 6625-01-030-7188

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-030-7188

### Circuit Current For Which Designed:

Dc

#### **Overall Length:**

1.810 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.320 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.320 inches

#### **Overall Height:**

1.750 inches

#### **Overall Width:**

1.750 inches

#### Scale Division Quantity:

50 single indicator single range

#### Mounting Stud Length:

0.530 inches

#### Furnished Items And Quantity:

Nut 2; washer 2

#### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

#### Dial Scale Marking Color:

Black single indicator single range

#### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

#### Meter Depth Behind Mounting Flange:

0.900 inches

#### Meter Body Diameter Behind Mounting Flange:

1.510 inches

#### **Background Color:**

White single indicator single range

#### **Pointer Color:**

Black single indicator single range

**Power Source:** 

External

#### Mounting Facility Type And Quantity:

4 threaded stud

#### Scale Graduation Type:

Linear single indicator single range

# NSN 6625-01-030-7188

Ammeter - Page 2 of 2



Measurement Range:
+0.0/+50.0 microamperes, dc single indicator single range
Mounting Stud Diameter:
0.112 inches
Features Provided:
Zero adjuster
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Supplementary Features:
Self-shielding movement
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

### Fiig:

A310a0