Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-031-5775

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
7.496 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.725 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
6.050 inches
Overall Height:
6.690 inches
Overall Width:
1.520 inches
Mounting Hole Diameter:
0.216 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertigh
Furnished Items And Quantity:
Nut 6; washer 6; 28 volt lamp 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.760 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Nonlinear single indicator single range **Measurement Range:** +4.0/+20.0 milliamperes, dc single indicator single range Meter Body Height Behind Mounting Flange: 0.925 inches **Features Provided:** Luminous scale marking and magnetic shield and self-illumination facility and zero adjuster **Criticality Code Justification:** Feat **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Tank 6-398-0-j jp-5 storage-ref Material: Stainless steel **Surface Treatment:** Enamel semigloss **Special Test Features:** Conforms to mil-m-10304 **Style Designator:** Rectangular flush mtg **Supplementary Features:** Resistance 10 ohms; response time 2 seconds **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A310a0