

View Online at <https://aerobasegroup.com/nsn/6625-01-031-5779>

Circuit Current For Which Designed:

Ac

Overall Length:

2.969 inches

Mounting Hole Diameter:

0.140 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Humidity resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Gasket 1

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

140.0 ohms per volt

Resonant Reed Quantity:

9

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.688 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+56.0/+64.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 solder stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 132.0 ac

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0