

View Online at <https://aerobasegroup.com/nsn/6625-01-032-2524>

Circuit Current For Which Designed:

Ac

Overall Length:

3.830 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

Between 3.490 inches and 3.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 7; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.630 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole and 3 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+110.0/+130.0 volts, ac single indicator single range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Sealed do not open

Material:

Steel

Surface Treatment:

Tin

Style Designator:

C1 round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0