## NSN 6625-01-033-9860

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-033-9860

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.990 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.557 inches
Overall Height:
3.974 inches
Overall Width:
5.108 inches
Mounting Stud Length:
0.500 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 8; lockwasher 6; shunt wire 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.298 inches
Meter Body Diameter Behind Mounting Flange:
2.634 inches
Movement Type:
Moving coil, permanent magnet
Background Color:

**Pointer Color:** 

Black single indicator all ranges

White single indicator all ranges

## NSN 6625-01-033-9860

Special Scale Meter - Page 2 of 2

**Fiig:** A310a0



Scale Marking:	
First scale, 250; 200; 150; 100; 90; 80; 70; 60; 50; second scale, 500; 400; 350; 300; 250; 200; level; noise temperature	re
Mounting Facility Type And Quantity:	
4 threaded stud	
Scale Graduation Type:	
Nonlinear single indicator all ranges	
Mounting Stud Diameter:	
0.134 inches	
Features Provided:	
External shunting and mirror scale and zero adjuster	
Movement Suspension Method:	
Taut band	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Special Features:	
Ruggedized; sealed	
Special Markings:	
On front, level; noise temperature	
Material:	
Plastic	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Paint	
Special Test Features:	
Complies with mil-m-10304	
Style Designator:	
Rectangular flush mtg	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	