

View Online at <https://aerobasegroup.com/nsn/6625-01-034-5232>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.563 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.315 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.315 inches

**Overall Height:**

1.788 inches

**Overall Width:**

1.788 inches

**Mounting Hole Diameter:**

0.121 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 4; lockwasher 4; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range and red single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.811 inches

**Meter Body Diameter Behind Mounting Flange:**

1.497 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0; 5mo; 1mo; 100kc; 10

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Features Provided:**

Magnetic shield

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 screw and 2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Chromate

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0