

View Online at <https://aerobasegroup.com/nsn/6625-01-036-8355>

Circuit Current For Which Designed:

Dc

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+500.0 ohms single indicator 1st range

Features Provided:

Zero adjuster

Meter Replacement Type:

Multimeter

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Ohms scale green, mils and volts black

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Mark iaw mil-m-13231

Supplementary Features:

Res 1560 ohms porm 10 pct

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0