

View Online at <https://aerobasegroup.com/nsn/6625-01-036-8356>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

3.260 inches

Overall Height:

0.905 inches

Overall Width:

2.467 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

8 single indicator single range

Environmental Protection:

Cold resistant and heat resistant

Distance Between Mounting Facility Centers:

Between 2.118 inches and 2.132 inches

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.118 inches

Meter Body Width Behind Mounting Flange:

1.700 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0 ctr scale; -left; +right; 9 graduation marks

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

0.610 inches

Features Provided:

Rfi shielding

Circuit Attachment Method And Quantity:

2 solder hook

Special Features:

Capacitive type term.

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular semi-flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0