

View Online at <https://aerobasegroup.com/nsn/6625-01-037-0058>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.03125 inches

Scale Division Quantity:

6 single indicator single range

Mounting Stud Length:

1.1875 inches

Overall Diameter:

2.250 inches

Distance Between Mounting Facility Centers:

1.000 inches

Furnished Items And Quantity:

Nut 4; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-10.0/+10.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.8125 inches

Meter Body Diameter Behind Mounting Flange:

2.03125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-30.0/+30.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.190 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Terminals are also mounting facilities

Special Markings:

Pos and neg signs

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0