

View Online at <https://aerobasegroup.com/nsn/6625-01-037-0058>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.03125 inches

**Scale Division Quantity:**

6 single indicator single range

**Mounting Stud Length:**

1.1875 inches

**Overall Diameter:**

2.250 inches

**Distance Between Mounting Facility Centers:**

1.000 inches

**Furnished Items And Quantity:**

Nut 4; lockwasher 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-10.0/+10.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.8125 inches

**Meter Body Diameter Behind Mounting Flange:**

2.03125 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp and 2 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-30.0/+30.0 amperes, ac single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Terminals are also mounting facilities

**Special Markings:**

Pos and neg signs

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Zinc

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0