

View Online at <https://aerobasegroup.com/nsn/6625-01-037-0432>

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 66.0 hertz

Internal Battery Accommodation:

Not included

Voltage Rating:

Between 100.0 volts and 240.0 volts

Output Frequency Rating:

10.0 megahertz

Mounting Method:

Bench

Measurement Type:

Frequency and period average and ratio

Frequency Range:

+0.000/+500.000 megahertz f1 input ratio and +0.000/+500.000 megahertz f2 input ratio

Accuracy Rating:

Porm time base

Gate Time:

Between 0.1 microseconds and 1000.0 seconds

Sensitivity Rating:

50 ohms per 40 mv rms, 1 megohm, no change

Period Range Step Quantity:

10 decade steps

Display Type:

Numeric readout tube

Display Digit Quantity:

11

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Remote Control Provisions:

Included

Solid State Feature:

Included

Inclosure Material And Location:

Plastic case

Plug-in Units Provision:

Included

Standard Frequency Output Feature:

Included

Frequency Accuracy/stability:

5 parts per 10000000000 per day

Output Frequency Waveform:

Sine wave

Frequency Output Amplitude:

1.0 volts peak to peak

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T297-a