## NSN 6625-01-037-5726

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-037-5726

| view Online at https://aerobasegroup.com/hist//oo25-01-057-5720  |
|--|
| Circuit Current For Which Designed:  |
| Ac   |
| Overall Length:  |
| 2.650 inches   |
| Mounting Hole Diameter:  |
| 0.125 inches   |
| Overall Diameter:  |
| 2.695 inches   |
| Mounting Bolt Circle Diameter:   |
| 2.440 inches   |
| Installation Design:   |
| Panel  |
| Mounting Arrangement Style:  |
| Three hole/stud bolt circle  |
| Dial Scale Marking Color:  |
| Black single indicator single range  |
| Accuracy In Percent:   |
| -2.0/+2.0 at full scale single indicator single range  |
| Meter Depth Behind Mounting Flange:  |
| 1.600 inches   |
| Meter Body Diameter Behind Mounting Flange:  |
| 2.210 inches   |
| Movement Type:   |
| Moving coil, permanent magnet  |
| Background Color:  |
| White single indicator single range  |
| Mounting Facility Type And Quantity:   |
| 3 unthreaded hole  |
| Measurement Range:   |
| +0.0/+300.0 amperes, ac single indicator single range  |
| Movement Suspension Method:  |
| Jewel pivot base   |
| Circuit Attachment Method And Quantity:  |
| 2 threaded stud  |
| Style Designator:  |
| Round flush mtg  |
| Test Data Document:  |
| 81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain        |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                          |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 6625-01-037-5726

Ammeter - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A310a0