

View Online at <https://aerobasegroup.com/nsn/6625-01-037-7872>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.858 inches

Overall Height:

0.906 inches

Overall Width:

2.124 inches

Mounting Hole Diameter:

0.117 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and vibration resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

1.915 inches

Furnished Items And Quantity:

Nut 2; lockwasher 2; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.979 inches

Meter Body Width Behind Mounting Flange:

1.697 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-2.0/+3.0 decibels single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

0.613 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Features:

Ruggedized

Special Markings:

On back, left turret marked +

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0