

View Online at <https://aerobasegroup.com/nsn/6625-01-038-6825>

Circuit Current For Which Designed:

Ac

Overall Length:

2.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.000 inches

Overall Width:

3.000 inches

Mounting Stud Length:

0.530 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.340 inches

Meter Body Diameter Behind Mounting Flange:

2.690 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0