

View Online at <https://aerobasegroup.com/nsn/6625-01-038-6827>

Circuit Current For Which Designed:

Dc

Overall Length:

2.253 inches

Overall Height:

2.878 inches

Overall Width:

5.000 inches

Scale Division Quantity:

25 single indicator all ranges

Environmental Protection:

Vibration resistant

Barrel Width:

4.572 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.594 inches

Meter Body Width Behind Mounting Flange:

4.572 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

1 bezel and 2 clip

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+25.0 volts, dc single indicator 2nd range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

4.317 inches

Meter Barrel Depth:

1.438 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Includes printed circuit card

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0