## NSN 6625-01-038-6835

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-038-6835

### **Circuit Current For Which Designed:**

Ac

### **Overall Length:**

11.000 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.376 inches

#### **Overall Height:**

Between 4.250 inches and 4.750 inches

#### **Overall Width:**

Between 4.250 inches and 4.750 inches

#### **Mounting Stud Length:**

Between 0.500 inches and 0.750 inches

#### Installation Design:

Panel

### **Mounting Arrangement Style:**

Four hole/stud rectangular/square

## **Dial Scale Marking Color:**

Black single indicator single range

## **Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

### **Meter Depth Behind Mounting Flange:**

9.000 inches

## **Meter Body Diameter Behind Mounting Flange:**

3.980 inches

## **Movement Type:**

Moving coil, permanent magnet

#### **Background Color:**

White single indicator single range

## **Mounting Facility Type And Quantity:**

4 threaded stud

#### **Measurement Range:**

+0.0/+4.0 kiloamperes, ac single indicator single range

### **Mounting Stud Diameter:**

0.250 inches

## **Movement Suspension Method:**

Jewel pivot base

### **Circuit Attachment Method And Quantity:**

2 threaded stud

#### **Style Designator:**

Rectangular flush mtg

# NSN 6625-01-038-6835

Ammeter - Page 2 of 2



#### **Test Data Document:**

81349-mil-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

Yes - demil/mli

Fiig:

A310a0