

View Online at <https://aerobasegroup.com/nsn/6625-01-038-6836>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.850 inches

**Mounting Hole Diameter:**

Between 0.143 inches and 0.157 inches

**Scale Division Quantity:**

100 single indicator single range

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Mtg hardware included

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, sys test, vapor, mod test

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Line at .5 red, segment between .2 and .3 transparent yellow

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiq:**

A310a0