

View Online at <https://aerobasegroup.com/nsn/6625-01-039-2702>

Overall Length:

17.000 inches

Overall Height:

3.500 inches

Overall Width:

13.500 inches

Vibration Resistance Range In Hertz:

Not rated

Individual Section Quantity:

2

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

P23-07421

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Top of cabinet/counter

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

50.0 megahertz 2nd output channel err-100

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

10.000 volts interstage preset

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms 2nd output channel err-100

Pulse Duration Per Channel:

10.000 nanoseconds 2nd output channel err-100

Pulse Rise Time Per Channel:

3.500 nanoseconds 2nd output channel err-100

Pulse Decay Time Per Channel:

3.500 nanoseconds 2nd output channel err-100

Polarity Per Channel:

Positive 2nd output channel err-100

Pulse Peak Amplitude Per Channel:

10.000 volts 2nd output channel err-100

Pulse Modulation Type Per Channel:

Amplitude 2nd output channel err-100

Signal Data Type Per Channel:

2nd output channel synchro err-100

Output Wave Shape:

Pulse, trigger

Indicator Device Type And Quantity:

1 light

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, coaxial front

Operating Ac Frequency In Hertz:

48.0 1st voltage

Connection Contact Type And Quantity:

4 receptacle, coaxial external

External Ac Operating Voltage In Volts:

220.0 2nd voltage

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200