## NSN 6625-01-039-2788

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-039-2788

Overall Length:
23.500 inches
Overall Height:
5.125 inches
Overall Width:
17.625 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 400.0 hertz
Joint Electronics Type Designation System Item Name:
Oscilloscope
Joint Electronics Type Designation System Item Type Number:
An/usm-425_v? 2
Voltage Rating:
115.0 volts
Beam Quantity:
1
Mounting Method:
Rack
Accuracy Range In Percent:
-1.0/+1.0
Screen Size:
8 by 10 centimeters
Sweep Circuits:
Included
Generator Driven Feature:
Included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+0.0/+100.0 megahertz
Single Trigger Sweep Duration:
500.0 milliseconds
Trigger Sweep Voltage Amplitude Rating:
100.0 volts
Trigger Sweep Polarity Switch:
Included
Amplifier Deflection Sensitivity Provision:

Vertical Deflection Sensitivity Voltage Rating:

Provided

5.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter

## NSN 6625-01-039-2788

Oscilloscope - Page 2 of 2



Input Intensity Modulation Feature:
Provided
Visual Blanking Sensitivity Voltage Rating:
5.0 volts
Plate Direct Connection Deflection Sensitivity Provision:
Not provided
Frequency Response Rating:
Not provided
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Amplitude Calibrating Voltage Waveform:
Square wave
Calibrating Peak To Peak Amplitude:
1.0 volts
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Special Features:
Oscilloscope is also rated for 230.0 volts
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T320-g