

View Online at <https://aerobasegroup.com/nsn/6625-01-039-5429>

Circuit Current For Which Designed:

Dc

Overall Length:

7.667 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.680 inches and 1.690 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 6.450 inches and 6.550 inches

Overall Height:

6.690 inches

Overall Width:

2.490 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

Between 0.375 inches and 0.780 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.720 inches

Meter Body Width Behind Mounting Flange:

5.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

Dual scale w/same info on both sides: degrees f x 10 to 2nd power

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.250 inches

Meter Body Height Behind Mounting Flange:

2.170 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0