

View Online at <https://aerobasegroup.com/nsn/6625-01-040-7658>

Circuit Current For Which Designed:

Dc

Overall Length:

3.044 inches

Overall Height:

3.000 inches

Overall Width:

2.286 inches

Mounting Hole Diameter:

0.166 inches

Scale Division Quantity:

50 single indicator single range

Distance Between Mounting Facility Centers:

2.686 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

34.0 ohms

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.538 inches

Meter Body Width Behind Mounting Flange:

2.258 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-500.0/+500.0 microamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.917 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0