

View Online at <https://aerobasegroup.com/nsn/6625-01-040-8592>

Test Type For Which Designed:

Parametric amplifier assembly, stalo assembly, vhf oscillator/amplifier, multiplier, power amplifier, power divider, isolator, circulator, bandpass filter, preselector filter, diplexer, stc attenuator, crossbar mixer, afc mixer, low power termination, high power dummy load, signal coupler, two-port coupler, afc coupler, tr limiter, waveguide switch, waveguide assemblies, rotary joint

Operating Test Capability:

Return loss, insertion loss, attenuation, coupling factor, directivity, gain, isolation: 0/3 db form 0.5 db, 3/15 db form 0.7 db, 15/30 db form 1.2 db, 30/50db form 2.0 db; noise figure: 0/9 db form 0.5 db, 9/12 db form 0.6 db, 12/18 db form 0.8 db, above 18 db form 1.3 db; frequency: dc/13.4 ghz form 1 count form oscillator stability, 31/33 ghz form 0.12 pct of reading; power: 200 khz/4.0 ghz form 0.5 pct full scale form 0.2 db, 31/33 ghz form 1.5 pct full scale

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T228-a