

View Online at <https://aerobasegroup.com/nsn/6625-01-041-3197>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.330 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Mounting Hole Diameter:

0.125 inches

Environmental Protection:

Hermetic and shock proof and vibration resistant

End Application:

Interference generator sg-886a-t/ur

Furnished Items And Quantity:

Nut 4; washer 2; gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and white single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.830 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving iron vane

Background Color:

Green single indicator single range and red single indicator single range and white single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Replace battery; a line at 35ua ref; operational

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Internal res 1 ko

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0