

View Online at <https://aerobasegroup.com/nsn/6625-01-041-6736>

Circuit Current For Which Designed:

Dc

Overall Length:

1.943 inches

Overall Height:

1.850 inches

Overall Width:

4.620 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

120 single indicator 1st range

Distance Between Mounting Facility Centers:

3.938 inches

Barrel Width:

2.000 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

5.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.818 inches

Meter Body Width Behind Mounting Flange:

1.124 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 3rd range

Measurement Range:

+0.6/+3.2 volts, dc single indicator 3rd range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

2.700 inches

Meter Barrel Depth:

1.419 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 solder lug

Special Markings:

Red and green section marked bat.; 0 dbm equals 0.775 v; f.S. 0-5 ma

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0