NSN 6625-01-042-7348

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-042-7348

Circuit Current For Which Decianed:
Circuit Current For Which Designed: Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
7.496 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.520 inches
Overall Width:
6.690 inches
Mounting Hole Diameter:
0.149 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Nut 6; lockwasher 2; flat washer 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
20.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range and green single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.760 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:

i dilita doloi

Black single indicator single range

NSN 6625-01-042-7348

Special Scale Meter - Page 2 of 2

Nonhardened

Paint

Surface Treatment:

Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

No Fiig: A310a0



Scale Marking:
0 deg, f; 15 deg; 30 deg; 45 deg; 60 deg; 70 deg, jp-5; 75 deg; 90 deg; 100 deg, md; 105 deg; 115 deg, ndf; 120 deg; 130 deg; 150
deg
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Green lines at 70 deg, 100 degrees and 115 deg
Material:
Steel
Nuclear Hardness Critical Feature: