

View Online at <https://aerobasegroup.com/nsn/6625-01-042-7365>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

7.496 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.050 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.725 inches

Overall Height:

1.520 inches

Overall Width:

6.690 inches

Mounting Hole Diameter:

0.216 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Mtg hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

20.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

6.126 inches

Meter Body Diameter Behind Mounting Flange:

4.895 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percent; 0; 20; 40; 60; 80; 100

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304 and mil-m-16034

Style Designator:

Rectangular flush mtg

Supplementary Features:

Vertical mount

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0