

View Online at <https://aerobasegroup.com/nsn/6625-01-043-6182>

Circuit Current For Which Designed:

Ac

Overall Length:

2.625 inches

Overall Height:

3.010 inches

Overall Width:

3.510 inches

Scale Division Quantity:

25 single indicator 2nd range

Mounting Stud Length:

0.560 inches

Distance Between Mounting Facility Centers:

3.125 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.045 inches

Meter Body Diameter Behind Mounting Flange:

2.960 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+50.0 volts, ac single indicator 2nd range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Term. Res 230 ohms porm 20 pct

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0