

View Online at <https://aerobasegroup.com/nsn/6625-01-044-4584>

**Circuit Current For Which Designed:**

Ac and dc

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

202.0 microamperes

**Dial Scale Marking Color:**

Pink single indicator 2nd range and white single indicator 2nd range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator all ranges

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator all ranges

**Pointer Color:**

White single indicator all ranges

**Power Source:**

External

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+340.0/+460.0 hertz single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Luminous scale marking and mirror scale and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

130 ohms res

**Special Markings:**

Fluorescent red lines at 115 vac, 27.75 vdc and 400 hz

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0