

View Online at <https://aerobasegroup.com/nsn/6625-01-044-4584>

Circuit Current For Which Designed:

Ac and dc

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

202.0 microamperes

Dial Scale Marking Color:

Pink single indicator 2nd range and white single indicator 2nd range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator all ranges

Pointer Color:

White single indicator all ranges

Power Source:

External

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+340.0/+460.0 hertz single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and mirror scale and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

130 ohms res

Special Markings:

Fluorescent red lines at 115 vac, 27.75 vdc and 400 hz

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0