## NSN 6625-01-046-7720

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-046-7720

| Ov   | erall Length:                                                            |  |  |
|------|--------------------------------------------------------------------------|--|--|
| 5.6  | 25 inches                                                                |  |  |
| Ce   | nter To Center Distance Between Mounting Facilities Parallel To Length:  |  |  |
| 3.3  | 375 inches                                                               |  |  |
| Се   | Center To Center Distance Between Mounting Facilities Parallel To Width: |  |  |
| 3.3  | 375 inches                                                               |  |  |
| Ov   | erall Height:                                                            |  |  |
| 4.3  | 344 inches                                                               |  |  |
| Ov   | erall Width:                                                             |  |  |
| 4.3  | 344 inches                                                               |  |  |
| Sca  | ale Division Quantity:                                                   |  |  |
| 50   | single indicator single range                                            |  |  |
| Мо   | ounting Stud Length:                                                     |  |  |
| 1.2  | 281 inches                                                               |  |  |
| Ins  | stallation Design:                                                       |  |  |
| Pai  | nel                                                                      |  |  |
| Мо   | Mounting Arrangement Style:                                              |  |  |
| Foo  | ur hole/stud rectangular/square                                          |  |  |
| Dia  | al Scale Marking Color:                                                  |  |  |
| Bla  | ack single indicator single range                                        |  |  |
| Ac   | curacy In Percent:                                                       |  |  |
| -2.0 | 0/+2.0 at full scale single indicator single range                       |  |  |
| Me   | Meter Depth Behind Mounting Flange:                                      |  |  |
| 3.5  | 500 inches                                                               |  |  |
| Me   | ter Body Diameter Behind Mounting Flange:                                |  |  |
| 3.7  | 750 inches                                                               |  |  |
| Мо   | ovement Type:                                                            |  |  |
| Мо   | ving coil, permanent magnet                                              |  |  |
| Ва   | ckground Color:                                                          |  |  |
| Wh   | nite single indicator single range                                       |  |  |
| Мо   | Mounting Facility Type And Quantity:                                     |  |  |
| 4 th | hreaded stud                                                             |  |  |
| Me   | asurement Range:                                                         |  |  |
| +5   | 5.0/+65.0 hertz single indicator single range                            |  |  |
| Мо   | ounting Stud Diameter:                                                   |  |  |
| 0.2  | 250 inches                                                               |  |  |

**Movement Suspension Method:** 

Jewel pivot base

**Circuit Attachment Method And Quantity:** 

2 threaded stud

Material:

Plastic

## NSN 6625-01-046-7720

Electrical Frequency Meter - Page 2 of 2



| Style | Desi | gnator: |
|-------|------|---------|
|       |      |         |

Rectangular flush mtg

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0