

View Online at <https://aerobasegroup.com/nsn/6625-01-047-4587>

Circuit Current For Which Designed:

Dc

Overall Length:

5.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.245 inches and 2.255 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.995 inches and 1.005 inches

Overall Height:

Between 1.400 inches and 1.420 inches

Overall Width:

Between 2.620 inches and 2.640 inches

Mounting Hole Diameter:

0.112 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Meter Depth Behind Mounting Flange:

4.800 inches

Meter Body Width Behind Mounting Flange:

Between 2.030 inches and 2.050 inches

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

3

Measurement Range:

+0.0/+1.9 volts single indicator single range

Meter Body Height Behind Mounting Flange:

Between 1.270 inches and 1.290 inches

Features Provided:

Overranging

Accuracy Rating:

30 days: p 20 degrees c to p 30 degrees c at 0.1 pct of reading porm 1 digit; 90 days: p 15 degrees c to p 35 degrees c at 0.2 pct of reading porm 1 digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

2 connector, receptacle

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0