

View Online at <https://aerobasegroup.com/nsn/6625-01-047-4881>

Circuit Current For Which Designed:

Ac

Overall Length:

2.220 inches

Overall Height:

2.730 inches

Overall Width:

3.150 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.450 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+25.000/+125.000 hertz

Sensitivity Rating:

10.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.010 inches

Meter Body Diameter Behind Mounting Flange:

2.190 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+10.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Nonglare glass and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Sign on rear of case

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0