NSN 6625-01-048-2102

Teletypewriter Test Set - Page 1 of 1



Width: 16.000 inches Length: 18.000 inches Ac Voltage Rating: 120.0 volts Frequency Rating: Between 47.0 hertz and 420.0 hertz	
Length: 18.000 inches Ac Voltage Rating: 120.0 volts Frequency Rating: Between 47.0 hertz and 420.0 hertz	
18.000 inches Ac Voltage Rating: 120.0 volts Frequency Rating: Between 47.0 hertz and 420.0 hertz	
Ac Voltage Rating: 120.0 volts Frequency Rating: Between 47.0 hertz and 420.0 hertz	
120.0 volts Frequency Rating: Between 47.0 hertz and 420.0 hertz	
Frequency Rating: Between 47.0 hertz and 420.0 hertz	
Between 47.0 hertz and 420.0 hertz	
Accessory Component Quantity:	
9	
Accessory Identifying Number:	
131704-0001 part no. And 131797-0001 part no. And 562883-0001 part no. And 131775-0002 part no. And 131835	i-000x part no.
Electrical Power Source Relationship:	
Operating	
Test Type For Which Designed:	
Fault isolation of replaceable modlules	
Operating Test Capability:	
Isolates eleven different set components; cannot isolate power supp	
Phase:	
Single	
Special Features:	
Test set contains a rom comparator to verify stored programs on rom module. Stowable, break-out, printhead alignr	ment box is provided fo
insertion in series wi printhead; provides control of ea individual digital stepper motor, used in printing, during adjust	t ment and alignment o
printhead assem bly	
Height:	
22.000 inches	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
T228-a	