NSN 6625-01-049-3455

Voltmeter - Page 1 of 2



| | ui o |
|---|------|
| View Online at https://aerobasegroup.com/nsn/6625-01-049-3455 | |
| Circuit Current For Which Designed: | |
| Dc | |
| Overall Length: | |
| 2.349 inches | |
| Mounting Hole Diameter: | |
| 0.125 inches | |
| Scale Division Quantity: | |
| 30 single indicator single range | |
| Overall Diameter: | |
| 2.695 inches | |
| Mounting Bolt Circle Diameter: | |
| 2.440 inches | |
| Indicator Type: | |
| Dial w/pointer | |
| Installation Design: | |
| Panel | |
| Mounting Arrangement Style: | |
| Three hole/stud bolt circle | |
| Sensitivity Rating: | |
| 1.0 milliamperes | |
| Dial Scale Marking Color: | |
| Black single indicator single range | |
| Accuracy In Percent: | |
| -1.0/+1.0 at full scale single indicator all ranges | |
| Meter Depth Behind Mounting Flange: | |
| 2.093 inches | |
| Meter Body Diameter Behind Mounting Flange: | |
| 2.187 inches | |
| Movement Type: | |
| | |

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+30.0 volts, dc single indicator single range

Features Provided:

Zero adjuster

NSN 6625-01-049-3455

Voltmeter - Page 2 of 2

A310a0



| Circuit Attachment Method And Quantity: |
|--|
| 2 threaded stud and 2 solder lug |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test sets, electronic systems, except specially designed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |