

View Online at <https://aerobasegroup.com/nsn/6625-01-049-3509>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Mounting Hole Diameter:

0.213 inches

Scale Division Quantity:

16 single indicator single range

Distance Between Mounting Facility Centers:

2.000 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

1.360 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+8.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Pointer is tubular

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Fan shape flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0