NSN 6625-01-049-3512

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-049-3512

Circuit Correct For Which Decimand
Circuit Current For Which Designed:
Dc Di la di Milita da la Maria de la Maria
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
7.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.728 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
6.000 inches
Overall Height:
1.530 inches
Overall Width:
6.700 inches
Mounting Hole Diameter:
0.220 inches
Scale Division Quantity:
30 single indicator single range
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
0.005 volts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.770 inches
Meter Body Width Behind Mounting Flange:
5.450 inches
Movement Type:
Moving coil, permanent magnet

White single indicator single range

Background Color:

NSN 6625-01-049-3512

Special Scale Meter - Page 2 of 2



Pointer Color:
Red single indicator single range
Scale Marking:
40; 60; 80; 200; 120; 140; 160; degrees
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On front, degrees
Material:
Steel
Steel Nuclear Hardness Critical Feature:
Nuclear Hardness Critical Feature:
Nuclear Hardness Critical Feature: Nonhardened
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip.
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:
Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Complies with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: