## NSN 6625-01-049-3515

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-049-3515

/iew Online at https://aerobasegroup.com/nsn/6625-01-049-3515
Circuit Current For Which Designed:
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
7.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
.530 inches
Overall Width:
5.700 inches
Nounting Hole Diameter:
0.220 inches
Scale Division Quantity:
0 single indicator single range
Environmental Protection:
Nirtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
vater resistant
Furnished Items And Quantity:
Jut 6; lockwasher 6; seal 1
ndicator Type:
Dial w/pointer
nstallation Design:
Panel
Iounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
0.005 volts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
1.0/+1.0 at full scale single indicator single range
Neter Depth Behind Mounting Flange:
5.770 inches
Aeter Body Width Behind Mounting Flange:
5.450 inches
lovement Type:
Aoving coil, permanent magnet
Background Color:
Vhite single indicator single range

## NSN 6625-01-049-3515

Special Scale Meter - Page 2 of 2



Pointer Color:
Red single indicator single range
Scale Marking:
0; 100; 200; 300; 400; 500; 600; 700; 800; 900; 1000; degrees
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On front, degrees
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0