

View Online at <https://aerobasegroup.com/nsn/6625-01-049-3518>

Circuit Current For Which Designed:

Dc

Overall Length:

7.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.719 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.000 inches

Overall Height:

1.524 inches

Overall Width:

6.688 inches

Mounting Hole Diameter:

0.221 inches

Scale Division Quantity:

40 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

10.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

5.750 inches

Meter Body Width Behind Mounting Flange:

4.834 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

0; 100; 200; 300; 400; 500; 600; 700; 800; psi

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.219 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0