NSN 6625-01-049-4281

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-049-4281

Reliability Indicator:
Not established
Overall Length:
2.260 inches
Mounting Hole Diameter:
0.157 inches
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.010 inches
Meter Body Diameter Behind Mounting Flange:
2.750 inches
Movement Type:
Movement Type: Moving coil, permanent magnet
Moving coil, permanent magnet
Moving coil, permanent magnet Background Color:
Moving coil, permanent magnet Background Color: White single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity:
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided:
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity:
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature:
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened
Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud Nuclear Hardness Critical Feature: Nonhardened Style Designator:

NSN 6625-01-049-4281

Ammeter - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0