NSN 6625-01-049-6060

Voltmeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-049-6060

| Dc |
|---|
| Overall Length: |
| 4.437 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.374 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.374 inches |
| Overall Height: |
| 4.421 inches |
| Overall Width: |
| 4.421 inches |
| Mounting Hole Diameter: |
| 0.250 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 3.750 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.960 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Scale Graduation Type: |

Measurement Range:

Linear single indicator single range

+0.0/+50.0 volts, dc single indicator single range

NSN 6625-01-049-6060

Voltmeter - Page 2 of 2



| Features Provided: |
|--|
| Zero adjuster |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, electronic equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |